



**Shaanxi Newstar Communications Equipment Co., Ltd**  
**Technical Type Specification Form**

**11.3 m Rx-only Antenna**



**Characteristics:**

- ✓ High gain, low sidelobe, high polarization identification rate;
- ✓ High precision reflection panel;
- ✓ Cassegrain, feedforward optional;
- ✓ C/Ku/X/L/S band optional;
- ✓ C/Ku common antenna, linear polarization, circular polarization, double linear&double circular optional;
- ✓ Modern design, convenient and fast installation&adjustment, strong anticorrosion, good stability;
- ✓ Trussed Az ( $\pm 90^\circ$ ) & Rotary platform Az ( $\pm 180^\circ$ ) optional;

**Accessories:**

Ground plot, foundation template, the anchor bolt, electric equipment, antenna controller, antenna drive, drive motor, limit switch, cable, connector;

**Optional:**

Deicing equipment, ODU support, electric polarization, lightning rod and wire, LNB;

**PERFORMANCE SPECIFICATIONS**

Type	NS-SEC-R1130	
Band	C-Band	KU-band
Operating Frequency, GHz	3.625~4.2	10.95~12.75
Gain, Mid-Band, dBi	51.72	60.83
Cross Pol differentiate, dB	$\geq 35$	$\geq 35$
Isolation, Tx to Rx, dB ( double linear&double circular optional; ) (dB)	$\geq 30$ (linear polarization) $\geq 20$ (circular polarization)	$\geq 30$ (linear polarization) $\geq 20$ (circular polarization)
Isolation (C/KU) (dB)	50	
VSWR	1.35:1	1.25:1
-3dB Beamwidth, Mid-Band	0.455°	0.156°
Feed interface	WR229G	WR75
General Sidelobe Envelope, dB	29-25log $\theta$ ( $1^\circ \leq \theta < 20^\circ$ )	

**MECHANICAL SPECIFICATIONS**

Antenna Diameter	11.3m
Antenna Type	Cassegrain, feedforward optional
Weight (Net)	Kg



**Shaanxi Newstar Communications Equipment Co., Ltd**  
**Technical Type Specification Form**

Antenna Kingpost	El. Over Az.
Azimuth Travel	$\pm 90^\circ$ or $\pm 180^\circ$
Elevation Travel	0°to 90°
Drive Mode	Motorized
<b><u>ENVIRONMENTAL SPECIFICATIONS</u></b>	
Wind speed of work	72kmph
Surface treatment	Steel parts: sand blasting and zinc-spray processing firstly,, then zinc yellow bottom paint and final white paint processg Aluminum parts: unoil firstly, then zinc yellow bottom paint and final white paint processing.